


## 12B229 Neutral

SKU: 200KWD127Z29



## Specificaties

|                        |        |
|------------------------|--------|
| Kettingsontwerp        | Duplex |
| Oppervlaktebehandeling | No     |
| Materiaal              | C45    |
| Spoed (inch)           | 3/4"   |
| Spoed (mm)             | 19.05  |
| ISO-standaardmaat      | 12B    |
| designation            | 12B229 |
| Boring diameter (mm)   |        |
| Eenheden               | pc     |
| numberOfTeethZ         | 29     |
| toothWidthMM           | 30.3   |
| pilotBoreDiameterMM    | 20     |
| pitchCircleDiameterMM  | 176.19 |
| tipCircleDiameterMM    | 184.4  |
| Geharde tanden         | Nee    |
| Gewicht (kg)           | 6.8    |
| weldedHub              | Nee    |
| taperBushSize          |        |
| hubDiamDnMM            | 120    |
| lengthInclHubLnMM      | 50     |

|                                               |           |
|-----------------------------------------------|-----------|
| toothWidthb1MM                                | 10.8      |
| SprocketType                                  | Standard  |
| BEAArticleNumber                              | 102360029 |
| ISOstandardSize2                              | ISO 606   |
| brandType(extraAttributeForNeutralIdentifier) | Extended  |
| Merk                                          | Neutral   |
| Materiaal                                     | C45       |
| Spoed (inch)                                  | 3/4"      |
| Spoed (mm)                                    | 19.05     |
| Boring diameter (mm)                          |           |
| Geharde tanden                                | Nee       |
| Gewicht (kg)                                  | 6.8       |

## Beschrijving

12B Duplex Z 29, Standard Neutral Sprockets

## Product URL

<https://aandrijftechniek.nl/product/12b229-neutral/>