


## 12B327 Neutral

SKU: 200KWTR127Z27



## Specificaties

|                        |         |
|------------------------|---------|
| Kettingsontwerp        | Triplex |
| Oppervlaktebehandeling | No      |
| Materiaal              | C45     |
| Spoed (inch)           | 3/4"    |
| Spoed (mm)             | 19.05   |
| ISO-standaardmaat      | 12B     |
| designation            | 12B327  |
| Boring diameter (mm)   |         |
| Eenheden               | pc      |
| numberOfTeethZ         | 27      |
| toothWidthMM           | 49.8    |
| pilotBoreDiameterMM    | 20      |
| pitchCircleDiameterMM  | 164.09  |
| tipCircleDiameterMM    | 172.3   |
| Geharde tanden         | Nee     |
| Gewicht (kg)           | 8.77    |
| weldedHub              | Nee     |
| taperBushSize          |         |
| hubDiamDnMM            | 120     |
| lengthInclHubLnMM      | 70      |

|                                               |           |
|-----------------------------------------------|-----------|
| toothWidthb1MM                                | 10.8      |
| SprocketType                                  | Standard  |
| BEAArticleNumber                              | 103360027 |
| ISOstandardSize2                              | ISO 606   |
| brandType(extraAttributeForNeutralIdentifier) | Extended  |
| Merk                                          | Neutral   |
| Materiaal                                     | C45       |
| Spoed (inch)                                  | 3/4"      |
| Spoed (mm)                                    | 19.05     |
| Boring diameter (mm)                          |           |
| Geharde tanden                                | Nee       |
| Gewicht (kg)                                  | 8.77      |

## Beschrijving

12B Triplex Z 27, Standard Neutral Sprockets

## Product URL

<https://aandrijftechniek.nl/product/12b327-neutral/>