

1680 XH 200 GATES PowerGrip??? Timing Endless timing belts GATES

SKU: 7G0XH1680-200



Specificaties

Gewicht (kg/m)	2.758
Spoed (mm)	22.2
Hoogte riem (mm)	11.4
Breedte riem (mm)	50.8
Spoorlengte (mm)	4267.2
Materiaal riem	Chloroprene
Koordmateriaal	Glass
Eenheden	pc
Riemprofiel	XH
numberOfTeethZ	192
toothWidthMM	6.4
Gewicht (kg)	2.758
beltLlengthCodeInch	168
beltWidthCodeInch	200
antistaticISO9563	Nee

Omschrijving (EN)	Gates?? classical synchronous PowerGrip??? Timing belts offer a maintenance-free, economical, and OE quality solution for your conventional timing drives such as chains and gears. Its application range extends from minimum drives (computer printers) to heavy-duty machinery (oil pumps, etc). The trapezoidal tooth profile makes this belt well suited for use in positioning applications. Fiberglass tensile cord provides high strength, excellent flex life and high resistance to elongation. Neoprene body provides protection against grime, grease, oil, moisture, and other contaminants. Nylon tooth facing provides a durable wear surface for long service life.
belLengthCodeInch	168
Minimale temperatuur (??C)	-30
Maximale temperatuur (??C)	+100
EAN-code	5412571264401
Aangepaste code	4010.3900.90
pitchLength(1_10 inch)	168
Status	Normal
oringColour	Black
Land van herkomst	GB
beltBackSide	Smooth
Tandvorm	Trapezoidal Design
sided	Single Sided
StatConductive	No
fabricMaterial	Nylon
beltEnd	Endless
sprockCompatable	PowerGrip
Merk	GATES
Gewicht (kg/m)	2.758
Spoed (mm)	22.2
Breedte riem (mm)	50.8
Materiaal riem	Chloroprene
Riemprofiel	XH
Gewicht (kg)	2.758
Minimale temperatuur (??C)	-30

Maximale temperatuur (°C)	+100
Land van herkomst	GB

Beschrijving

1680 XH 200 GATES PowerGrip??? Timing Endless timing belts

Product URL

<https://aandrijftechniek.nl/product/1680-xh-200-gates-powergrip-timing-endless-timing-belts-gates/>