

16B112 30 Neutral

SKU: 24116Z12B30H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
ISO-standaardmaat	16B
designation	16B112 30
Boring diameter (mm)	30
Eenheden	pc
numberOfTeethZ	12
toothWidthMM	16.2
pitchCircleDiameterMM	98.14
tipCircleDiameterMM	109.7
Geharde tanden	Ja
Gewicht (kg)	1.35
weldedHub	Nee
taperBushSize	
hubDiamDnMM	69
lengthInclHubLnMM	40
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101380012030
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
Boring diameter (mm)	30
Geharde tanden	Ja
Gewicht (kg)	1.35

Beschrijving

16B Simplex Z 12, Standard Finished Bore 30 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/16b112-30-neutral/>