

16B112 Neutral

SKU: 200KHM1611Z12



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
ISO-standaardmaat	ISO 606
designation	16B112
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	12
toothWidthMM	16.2
pilotBoreDiameterMM	16
pitchCircleDiameterMM	98.14
tipCircleDiameterMM	109.7
Geharde tanden	Ja
Gewicht (kg)	1.43
weldedHub	Nee
taperBushSize	
hubDiamDnMM	69
lengthInclHubLnMM	40

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191380012
ISOstandardSize2	16B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	1.43

Beschrijving

ISO 606 Simplex Z 12, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/16b112-neutral-2/>