

16B116 Neutral

SKU: 200KHM1611Z16



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
ISO-standaardmaat	ISO 606
designation	16B116
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	16
toothWidthMM	16.2
pilotBoreDiameterMM	20
pitchCircleDiameterMM	130.2
tipCircleDiameterMM	141.8
Geharde tanden	Ja
Gewicht (kg)	3.14
weldedHub	Nee
taperBushSize	
hubDiamDnMM	100
lengthInclHubLnMM	45

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191380016
ISOstandardSize2	16B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	3.14

Beschrijving

ISO 606 Simplex Z 16, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/16b116-neutral-2/>