

16B124 30 Neutral

SKU: 24116Z24B30H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
ISO-standaardmaat	16B
designation	16B124 30
Boring diameter (mm)	30
Eenheden	pc
numberOfTeethZ	24
toothWidthMM	16.2
pitchCircleDiameterMM	194.59
tipCircleDiameterMM	206.2
Geharde tanden	Ja
Gewicht (kg)	4.68
weldedHub	Nee
taperBushSize	
hubDiamDnMM	80
lengthInclHubLnMM	50
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M6
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101380024030
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
Boring diameter (mm)	30
Geharde tanden	Ja
Gewicht (kg)	4.68

Beschrijving

16B Simplex Z 24, Standard Finished Bore 30 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/16b124-30-neutral/>