

16B124 32 Neutral

SKU: 24116Z24B32H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
ISO-standaardmaat	16B
designation	16B124 32
Boring diameter (mm)	32
Eenheden	pc
numberOfTeethZ	24
toothWidthMM	16.2
pitchCircleDiameterMM	194.59
tipCircleDiameterMM	206.2
Geharde tanden	Ja
Gewicht (kg)	5.37
weldedHub	Nee
taperBushSize	
hubDiamDnMM	100
lengthInclHubLnMM	50
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M8
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101380024032
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
Boring diameter (mm)	32
Geharde tanden	Ja
Gewicht (kg)	5.37

Beschrijving

16B Simplex Z 24, Standard Finished Bore 32 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/16b124-32-neutral/>