

16B124 Neutral

SKU: 200KHM1611Z24



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
ISO-standaardmaat	ISO 606
designation	16B124
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	24
toothWidthMM	16.2
pilotBoreDiameterMM	20
pitchCircleDiameterMM	194.59
tipCircleDiameterMM	206.2
Geharde tanden	Ja
Gewicht (kg)	5.86
weldedHub	Nee
taperBushSize	
hubDiamDnMM	110
lengthInclHubLnMM	50

SprocketType	Standard Induction hardened teeth
BEAArticleNumber	191380024
ISOstandardSize2	16B
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
Boring diameter (mm)	
Geharde tanden	Ja
Gewicht (kg)	5.86

Beschrijving

ISO 606 Simplex Z 24, Standard Induction hardened teeth Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/16b124-neutral-2/>