

16B125 35 Neutral

SKU: 24116Z25B35H



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
ISO-standaardmaat	16B
designation	16B125 35
Boring diameter (mm)	35
Eenheden	pc
numberOfTeethZ	25
toothWidthMM	16.2
pitchCircleDiameterMM	202.66
tipCircleDiameterMM	214.2
Geharde tanden	Ja
Gewicht (kg)	5.6
weldedHub	Nee
taperBushSize	
hubDiamDnMM	100
lengthInclHubLnMM	50
keywayAccToDIN6885/1	Ja

boreDiameterTol	H7
keywayTol	H9
setscrewSize	M8
SprocketType	Standard Finished Bore
BEAArticleNumber	SB101380025035
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"
Spoed (mm)	25.4
Boring diameter (mm)	35
Geharde tanden	Ja
Gewicht (kg)	5.6

Beschrijving

16B Simplex Z 25, Standard Finished Bore 35 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/16b125-35-neutral/>