


# 16B228 Neutral

SKU: 200KWD1611Z28



## Specificaties

|                        |        |
|------------------------|--------|
| Kettingsontwerp        | Duplex |
| Oppervlaktebehandeling | No     |
| Materiaal              | C45    |
| Spoed (inch)           | 1"     |
| Spoed (mm)             | 25.4   |
| ISO-standaardmaat      | 16B    |
| designation            | 16B228 |
| Boring diameter (mm)   |        |
| Eenheden               | pc     |
| numberOfTeethZ         | 28     |
| toothWidthMM           | 47.7   |
| pilotBoreDiameterMM    | 25     |
| pitchCircleDiameterMM  | 226.85 |
| tipCircleDiameterMM    | 238.4  |
| Geharde tanden         | Nee    |
| Gewicht (kg)           | 15.38  |
| weldedHub              | Nee    |
| taperBushSize          |        |
| hubDiamDnMM            | 130    |
| lengthInclHubLnMM      | 70     |

|                                               |           |
|-----------------------------------------------|-----------|
| toothWidthb1MM                                | 15.8      |
| SprocketType                                  | Standard  |
| BEAArticleNumber                              | 102380028 |
| ISOstandardSize2                              | ISO 606   |
| brandType(extraAttributeForNeutralIdentifier) | Extended  |
| Merk                                          | Neutral   |
| Materiaal                                     | C45       |
| Spoed (inch)                                  | 1"        |
| Spoed (mm)                                    | 25.4      |
| Boring diameter (mm)                          |           |
| Geharde tanden                                | Nee       |
| Gewicht (kg)                                  | 15.38     |

# Beschrijving

16B Duplex Z 28, Standard Neutral Sprockets

# Product URL

<https://aandrijftechniek.nl/product/16b228-neutral/>