

20B125 Neutral

SKU: 200TWM2012Z25



Specificaties

Kettingsontwerp	Simplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	1"1/4
Spoed (mm)	31.75
ISO-standaardmaat	20B
designation	20B125
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	25
toothWidthMM	18.5
pitchCircleDiameterMM	253.33
tipCircleDiameterMM	268.4
Geharde tanden	Nee
Gewicht (kg)	9.5
weldedHub	Nee
execution	1
taperBushSize	2517
hubDiamDnMM	120
lengthInclHubLnMM	44

SprocketType	Standard Taper Bush
BEAArticleNumber	381400025
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"1/4
Spoed (mm)	31.75
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	9.5

Beschrijving

20B Simplex Z 25, Standard Taper Bush 2517 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/20b125-neutral-2/>