

20B225 Neutral

SKU: 200TWD2012Z25



Specificaties

Kettingsontwerp	Duplex
Oppervlaktebehandeling	NO
Materiaal	C45
Spoed (inch)	1"1/4
Spoed (mm)	31.75
ISO-standaardmaat	20B
designation	20B225
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	25
toothWidthMM	54.6
pitchCircleDiameterMM	253.33
tipCircleDiameterMM	268.4
Geharde tanden	Nee
Gewicht (kg)	10.5
weldedHub	Nee
execution	2
taperBushSize	3030
hubDiamDnMM	140
lengthInclHubLnMM	76

toothWidthb1MM	18.2
SprocketType	Standard Taper Bush
BEAArticleNumber	382400025
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"1/4
Spoed (mm)	31.75
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	10.5

Beschrijving

20B Duplex Z 25, Standard Taper Bush 3030 Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/20b225-neutral-2/>