

20B308 Neutral

SKU: 200KWTR2012Z8



Specificaties

Kettingsontwerp	Triplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	1"1/4
Spoed (mm)	31.75
ISO-standaardmaat	20B
designation	20B308
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	8
toothWidthMM	91
pilotBoreDiameterMM	25
pitchCircleDiameterMM	82.96
tipCircleDiameterMM	96
Geharde tanden	Nee
Gewicht (kg)	2.15
weldedHub	Nee
taperBushSize	
hubDiamDnMM	53
lengthInclHubLnMM	110

toothWidthb1MM	18.2
SprocketType	Standard
BEAArticleNumber	103400008
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"1/4
Spoed (mm)	31.75
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	2.15

Beschrijving

20B Triplex Z 8, Standard Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/20b308-neutral/>