

20B322 Neutral

SKU: 60574001



Specificaties

Kettingsontwerp	Triplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	1"1/4
Spoed (mm)	31.75
ISO-standaardmaat	20B
designation	20B322
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	22
toothWidthMM	91
pilotBoreDiameterMM	30
pitchCircleDiameterMM	223.11
tipCircleDiameterMM	238.1
Geharde tanden	Nee
Gewicht (kg)	25.64
weldedHub	Nee
taperBushSize	
hubDiamDnMM	140
lengthInclHubLnMM	115

toothWidthb1MM	18.2
SprocketType	Standard
BEAArticleNumber	103400022
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"1/4
Spoed (mm)	31.75
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	25.64

Beschrijving

20B Triplex Z 22, Standard Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/20b322-neutral-2/>