


20B326 Neutral

SKU: 200KWTR2012Z26



Specificaties

Kettingsontwerp	Triplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	1"1/4
Spoed (mm)	31.75
ISO-standaardmaat	20B
designation	20B326
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	26
toothWidthMM	91
pilotBoreDiameterMM	30
pitchCircleDiameterMM	263.4
tipCircleDiameterMM	278.4
Geharde tanden	Nee
Gewicht (kg)	36.23
weldedHub	Nee
taperBushSize	
hubDiamDnMM	150
lengthInclHubLnMM	115

toothWidthb1MM	18.2
SprocketType	Standard
BEAArticleNumber	103400026
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"1/4
Spoed (mm)	31.75
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	36.23

Beschrijving

20B Triplex Z 26, Standard Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/20b326-neutral/>