

## 24B134 Neutral

SKU: 200KWM2416Z34



### Specificaties

|                        |         |
|------------------------|---------|
| Kettingsontwerp        | Simplex |
| Oppervlaktebehandeling | No      |
| Materiaal              | Steel   |
| Spoed (inch)           | 1"1/2   |
| Spoed (mm)             | 38.1    |
| ISO-standaardmaat      | 24B     |
| designation            | 24B134  |
| Boring diameter (mm)   |         |
| Eenheden               | pc      |
| numberOfTeethZ         | 34      |
| toothWidthMM           | 24.1    |
| pilotBoreDiameterMM    | 30      |
| pitchCircleDiameterMM  | 412.83  |
| tipCircleDiameterMM    | 428     |
| Geharde tanden         | Nee     |
| Gewicht (kg)           | 28.38   |
| weldedHub              | Ja      |
| taperBushSize          |         |
| hubDiamDnMM            | 150     |
| lengthInclHubLnMM      | 60      |

|                                                      |           |
|------------------------------------------------------|-----------|
| <b>SprocketType</b>                                  | Standard  |
| <b>BEAArticleNumber</b>                              | 101420034 |
| <b>ISOstandardSize2</b>                              | ISO 606   |
| <b>brandType(extraAttributeForNeutralIdentifier)</b> | Extended  |
| <b>Merk</b>                                          | Neutral   |
| <b>Materiaal</b>                                     | Steel     |
| <b>Spoed (inch)</b>                                  | 1"1/2     |
| <b>Spoed (mm)</b>                                    | 38.1      |
| <b>Boring diameter (mm)</b>                          |           |
| <b>Geharde tanden</b>                                | Nee       |
| <b>Gewicht (kg)</b>                                  | 28.38     |

## Beschrijving

24B Simplex Z 34, Standard Neutral Sprockets

## Product URL

<https://aandrijftechniek.nl/product/24b134-neutral/>