

24B310 Neutral

SKU: 200KWTR2416Z10



Specificaties

Kettingsontwerp	Triplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	1"1/2
Spoed (mm)	38.1
ISO-standaardmaat	24B
designation	24B310
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	10
toothWidthMM	120.3
pilotBoreDiameterMM	25
pitchCircleDiameterMM	123.29
tipCircleDiameterMM	137
Geharde tanden	Nee
Gewicht (kg)	7.45
weldedHub	Nee
taperBushSize	
hubDiamDnMM	80
lengthInclHubLnMM	140

toothWidthb1MM	23.6
SprocketType	Standard
BEAArticleNumber	103420010
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"1/2
Spoed (mm)	38.1
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	7.45

Beschrijving

24B Triplex Z 10, Standard Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/24b310-neutral/>