

24B313 Neutral

SKU: 200KWTR2416Z13



Specificaties

Kettingsontwerp	Triplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	1"1/2
Spoed (mm)	38.1
ISO-standaardmaat	24B
designation	24B313
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	13
toothWidthMM	120.3
pilotBoreDiameterMM	30
pitchCircleDiameterMM	159.18
tipCircleDiameterMM	173
Geharde tanden	Nee
Gewicht (kg)	15.02
weldedHub	Nee
taperBushSize	
hubDiamDnMM	114
lengthInclHubLnMM	150

toothWidthb1MM	23.6
SprocketType	Standard
BEAArticleNumber	103420013
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"1/2
Spoed (mm)	38.1
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	15.02

Beschrijving

24B Triplex Z 13, Standard Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/24b313-neutral/>