

24B320 Neutral

SKU: 200KWTR2416Z20



Specificaties

Kettingsontwerp	Triplex
Oppervlaktebehandeling	No
Materiaal	C45
Spoed (inch)	1"1/2
Spoed (mm)	38.1
ISO-standaardmaat	24B
designation	24B320
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	20
toothWidthMM	120.3
pilotBoreDiameterMM	30
pitchCircleDiameterMM	243.57
tipCircleDiameterMM	257.5
Geharde tanden	Nee
Gewicht (kg)	39.57
weldedHub	Nee
taperBushSize	
hubDiamDnMM	160
lengthInclHubLnMM	150

toothWidthb1MM	23.6
SprocketType	Standard
BEAArticleNumber	103420020
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	C45
Spoed (inch)	1"1/2
Spoed (mm)	38.1
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	39.57

Beschrijving

24B Triplex Z 20, Standard Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/24b320-neutral/>