

## 24B327 Neutral

SKU: 200KWTR2416Z27



### Specificaties

|                        |         |
|------------------------|---------|
| Kettingsontwerp        | Triplex |
| Oppervlaktebehandeling | No      |
| Materiaal              | Steel   |
| Spoed (inch)           | 1"1/2   |
| Spoed (mm)             | 38.1    |
| ISO-standaardmaat      | 24B     |
| designation            | 24B327  |
| Boring diameter (mm)   |         |
| Eenheden               | pc      |
| numberOfTeethZ         | 27      |
| toothWidthMM           | 120.3   |
| pilotBoreDiameterMM    | 40      |
| pitchCircleDiameterMM  | 328.19  |
| tipCircleDiameterMM    | 343     |
| Geharde tanden         | Nee     |
| Gewicht (kg)           | 71.88   |
| weldedHub              | Ja      |
| taperBushSize          |         |
| hubDiamDnMM            | 160     |
| lengthInclHubLnMM      | 150     |

|                                               |           |
|-----------------------------------------------|-----------|
| toothWidthb1MM                                | 23.6      |
| SprocketType                                  | Standard  |
| BEAArticleNumber                              | 103420027 |
| ISOstandardSize2                              | ISO 606   |
| brandType(extraAttributeForNeutralIdentifier) | Extended  |
| Merk                                          | Neutral   |
| Materiaal                                     | Steel     |
| Spoed (inch)                                  | 1"1/2     |
| Spoed (mm)                                    | 38.1      |
| Boring diameter (mm)                          |           |
| Geharde tanden                                | Nee       |
| Gewicht (kg)                                  | 71.88     |

# Beschrijving

24B Triplex Z 27, Standard Neutral Sprockets

# Product URL

<https://aandrijftechniek.nl/product/24b327-neutral/>