


32B230 Neutral

SKU: 200KWD3219Z30



Specificaties

Kettingsontwerp	Duplex
Oppervlaktebehandeling	No
Materiaal	Steel
Spoed (inch)	2"
Spoed (mm)	50.8
ISO-standaardmaat	32B
designation	32B230
Boring diameter (mm)	
Eenheden	pc
numberOfTeethZ	30
toothWidthMM	87.4
pilotBoreDiameterMM	40
pitchCircleDiameterMM	486
tipCircleDiameterMM	508
Geharde tanden	Nee
Gewicht (kg)	120.41
weldedHub	Ja
taperBushSize	
hubDiamDnMM	200
lengthInclHubLnMM	120

toothWidthb1MM	28.8
SprocketType	Standard
BEAArticleNumber	102460030
ISOstandardSize2	ISO 606
brandType(extraAttributeForNeutralIdentifier)	Extended
Merk	Neutral
Materiaal	Steel
Spoed (inch)	2"
Spoed (mm)	50.8
Boring diameter (mm)	
Geharde tanden	Nee
Gewicht (kg)	120.41

Beschrijving

32B Duplex Z 30, Standard Neutral Sprockets

Product URL

<https://aandrijftechniek.nl/product/32b230-neutral/>