

3M224JB/2 GATES Polyflex??? JB??? Banded V-belts GATES

SKU: 4G0003M224/2



Specificaties

| | |
|--------------------------|--|
| Type riem | Wide angle V-belts PU |
| Hoogte riem (mm) | 2.3 |
| Breedte riem (mm) | 3 |
| Antistatisch | Ja |
| Spoorlengte (mm) | 224 |
| Materiaal riem | PU |
| Koordmateriaal | Polyester |
| Eenheden | pc |
| Riemprofiel | 3M/JB |
| Gewicht (kg) | 0.005 |
| Omschrijving (EN) | <p>Polyflex??? JB??? is synonymous with high power density in small spaces. Developed by Gates and produced to patented manufacturing processes, these belts provide more load-carrying capacity at higher speeds to small multiple V-belt precision drives. This results in significant cost savings and improved design freedom. Polyflex??? JB??? belts are recommended for use on bench type milling machines, lathe drives, woodworking and metalworking machine spindle drives, computer peripheral equipment, small blowers, etc. They are available in 3M-JB, 5M-JB, 7M-JB and 11M-JB sections. High modulus polyurethane compound with a high friction coefficient. The polyurethane compound resists fatigue, wear and ozone. Temperature Range: -54??C to +85??C (-65??F to +185??F).</p> |

| | |
|-----------------------------------|----------------------------|
| Minimale temperatuur (??C) | -54 |
| Maximale temperatuur (??C) | +85 |
| EAN-code | 5414465251733 |
| Aangepaste code | 3926.9097.90 |
| numberOfRibs | 2 |
| Status | Article to be discontinued |
| oringColour | BLACK |
| Land van herkomst | US |
| Constructie | Banded |
| beltInside | Smooth |
| beltBackSide | Notched |
| Hoek | 60 |
| Merk | GATES |

Beschrijving

3M224JB/2 GATES Polyflex??? JB??? Banded V-belts

Product URL

<https://aandrijftechniek.nl/product/3m224jb-2-gates-polyflex-jb-banded-v-belts-gates/>