

40001431 IWIS Roller chains IWIS

SKU: 10000TR3219



Specificaties

Kettingsontwerp	Triplex
Kettingsmering	ip2
Corrosiebestendig	Nee
Rechte zijplaten	Nee
Minimale breekbelasting volgens ISO (kN)	670
Gewicht (kg/m)	29.6
Materiaal	Steel
Spoed (inch)	2
Spoed (mm)	50.8
Maximale rollerdikte (D1) (mm)	29.21
Breedte tussen binnenplaten (mm)	30.95
Maximale pennendiameter (D2) (mm)	17.81
Maximale hoogte binnenplaat (H2) (mm)	42.3

Minimale breekbelasting leverancier (kN)	795
Dwarssteek (Pt) (mm)	58.55
Onderhoudsvrij	Nee
ISO-standaardmaat	32B
ISO-standaard	ISO 606 BS
Lageroppervlakte (cm??)	24.15
Omschrijving (EN)	JWIS Roller chains are characterised by an above-average service life due to excellent wear resistance, high consistency, matchless precision and a considerably higher breaking strength and fatigue strength than required by ISO standard. All iwis chains are pre-stretched and are provided with a highly efficient initial lubrication. Highlights: - Only high-quality heat-treated and case-hardened steel is used with stringent specifications for materials analysis, tolerances and surface quality - Each chain part is manufactured a million times daily to the same precision and is monitored using SPC (statistical process control) - All chain parts are heat-treated, in some cases using special processes to optimize quality characteristics - Modern production technologies ensure consistent geometry and superior surface quality - Chains are checked for dimensional accuracy, length tolerance and flexibility, plus for the press fit joins on pins, outer plates and bush, and inner plate - Our high quality assurance standards comply with the requirements of ISO 9001:2006 - For special applications: surface coatings, special lubricants, special materials (e.g. corrosion-resistant)
accToISO606kN	670
accToANSIkN	670
Merk	IWIS
Gewicht (kg/m)	29.6
Materiaal	Steel
Spoed (inch)	2
Spoed (mm)	50.8

Beschrijving

40001431 IWIS Roller chains

Product URL

<https://aandrijftechniek.nl/product/40001431-iwis-roller-chains-iwis/>