

50009405 IWIS Roller chains IWIS

SKU: 10000G53HZ



Specificaties

Kettingsontwerp	Simplex
Kettingsmering	ip2
Corrosiebestendig	Nee
Rechte zijplaten	Ja
Gewicht (kg/m)	0.34
Materiaal	Steel
Spoed (inch)	0.31496062992126
Spoed (mm)	8
Maximale rollerdikte (D1) (mm)	5
Breedte tussen binnenplaten (mm)	4.76
Maximale pennendiameter (D2) (mm)	3.15
Maximale hoogte binnenplaat (H2) (mm)	7.6
Minimale breekbelasting leverancier (kN)	8.5
Onderhoudsvrij	Nee

ISO-standaardmaat	05B
ISO-standaard	worksstandard
Lageroppervlakte (cm??)	0.25
Omschrijving (EN)	JWIS Roller chains are characterised by an above-average service life due to excellent wear resistance, high consistency, matchless precision and a considerably higher breaking strength and fatigue strength than required by ISO standard. All iwis chains are pre-stretched and are provided with a highly efficient initial lubrication. Highlights: - Only high-quality heat-treated and case-hardened steel is used with stringent specifications for materials analysis, tolerances and surface quality - Each chain part is manufactured a million times daily to the same precision and is monitored using SPC (statistical process control) - All chain parts are heat-treated, in some cases using special processes to optimize quality characteristics - Modern production technologies ensure consistent geometry and superior surface quality - Chains are checked for dimensional accuracy, length tolerance and flexibility, plus for the press fit joins on pins, outer plates and bush, and inner plate - Our high quality assurance standards comply with the requirements of ISO 9001:2006 - For special applications: surface coatings, special lubricants, special materials (e.g. corrosion-resistant)
Merk	IWIS
Gewicht (kg/m)	0.34
Materiaal	Steel
Spoed (inch)	0.31496062992126
Spoed (mm)	8

Beschrijving

50009405 IWIS Roller chains

Product URL

<https://aandrijftechniek.nl/product/50009405-iwis-roller-chains-iwis/>