

50021145 IWIS Roller chains IWIS

SKU: 11000M128A



Specificaties

Kettingsontwerp	Simplex
Kettingsmering	ip4
Corrosiebestendig	Nee
Rechte zijplaten	Nee
Minimale breekbelasting volgens ISO (kN)	31.3
Gewicht (kg/m)	1.47
Materiaal	Steel
Spoed (inch)	0.75
Spoed (mm)	19.05
Maximale rollerdikte (D1) (mm)	11.91
Breedte tussen binnenplaten (mm)	12.7
Maximale pennendiameter (D2) (mm)	5.96
Maximale hoogte binnenplaat (H2) (mm)	18.09

Minimale breekbelasting leverancier (kN)	42
Onderhoudsvrij	Nee
ISO-standaardmaat	60
ISO-standaard	ISO 606 ANSI
Lageroppervlakte (cm²)	1.06
Omschrijving (EN)	JWIS Roller chains are characterised by an above-average service life due to excellent wear resistance, high consistency, matchless precision and a considerably higher breaking strength and fatigue strength than required by ISO standard. All iwis chains are pre-stretched and are provided with a highly efficient initial lubrication. iwis SL series chains (Super Longlife) have pins with an extremely hard surface. This special design shows outstanding characteristics: Highest wear resistance, a prolonged service life, high breaking and fatigue strength, low susceptibility to deficient operational lubrication, corrosion and frictional corrosion in the chain links. Highlights: - Only high-quality heat-treated and case-hardened steel is used with stringent specifications for materials analysis, tolerances and surface quality - Each chain part is manufactured a million times daily to the same precision and is monitored using SPC (statistical process control) - All chain parts are heat-treated, in some cases using special processes to optimize quality characteristics - Modern production technologies ensure consistent geometry and superior surface quality - Chains are checked for dimensional accuracy, length tolerance and flexibility, plus for the press fit joints on pins, outer plates and bush, and inner plate - Our high quality assurance standards comply with the requirements of ISO 9001:2006 - For special applications: surface coatings, special lubricants, special materials (e.g. corrosion-resistant)
accToISO606kN	31.3
accToANSIkN	31.3
Merk	IWIS
Gewicht (kg/m)	1.47
Materiaal	Steel
Spoed (inch)	0.75
Spoed (mm)	19.05

Beschrijving

50021145 IWIS Roller chains

Product URL

<https://aandrijftechniek.nl/product/50021145-iwis-roller-chains-iwis/>