

5VP3550/5 15JP9000/5 GATES Predator™ Powerband™ Banded V-belts GATES

SKU: 4G0005V3550/5P

Specificaties

| | |
|--------------------------------------|----------------|
| Gewicht (kg/m) | 13.393 |
| Type riem | Narrow wrapped |
| Buitenlengte (mm) | 9022 |
| Hoogte riem (mm) | 13 |
| Breedte riem (mm) | 80 |
| Standaard | RMA |
| Minimale diameter pulley (mm) | 140 |
| Antistatisch | Nee |
| Binnenlengte (mm) | 8940 |
| Spoorlengte (mm) | 9000 |
| Materiaal riem | Chloroprene |
| Koormateriaal | Aramid |
| Eenheden | pc |
| Riemprofiel | 5VP/15JP |
| Ribsteek (S) (mm) | 17.5 |
| Ribbreedte riem (mm) | 5 |
| Gewicht (kg) | 13.393 |

| | |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Omschrijving (EN) | Gates' Predator™ PowerBand™ belt design offers a solution for drives where single belts vibrate, turn over or jump off the pulleys. It consists of several V-belts joined together by a permanent, high-strength tie band allowing the belts to work together as one unit. The Predator™ Powerband™ belt is especially designed for demanding applications and harsh environments and offers a high resistance to vibration. Specifically designed for high-demand applications, the extra heavy-duty belt construction provides extraordinary high impact strength, capacity and wear resistance. Aramid Tensile Cords combine limited stretch with extraordinary strength and durability that is pound-for-pound stronger than steel. Bareback Cover resists debris and allows the belt to slip under extreme shock load conditions, reducing heat build-up and prolonging belt life. Multiple layer Tie Band provides excellent lateral rigidity to prevent belts from turning over or from coming off of the drive. |
| Minimale temperatuur (°C) | -30 |
| Maximale temperatuur (°C) | +60 |
| EAN-code | 5414465586866 |
| Aangepaste code | 4010.3900.90 |
| pitchLength(1_10 inch) | 3543.3070866142 |
| numberOfRibs | 5 |
| Status | Normal |
| oringColour | BLACK |
| Land van herkomst | PL |
| Constructie | Bandless |
| beltInside | Smooth |
| beltBackSide | Smooth |
| OC(mm) | 9037 |
| Hoek | 40 |
| Bereik/ROHS-conformiteit | REACH and RoHS 2 |
| ISO1-standaard | 1813 |
| SEOattribute | 5VP3550/515JP9000/5 |
| Merk | GATES |

Beschrijving

5VP3550/5 15JP9000/5 GATES Predator™ Powerband™ Banded V-belts

Product URL

<https://aandrijftechniek.nl/product/5vp3550-5-15jp9000-5-gates-predator-powerband-banded-v-belts-gates/>