

5VX1500/3 GATES Quad-Power™ 4 Powerband™ Banded V-belts GATES

SKU: 4G0005VX1500/3

Specificaties

Gewicht (kg/m)	3.388
Type riem	Narrow raw edge
Buitenlengte (mm)	3832
Hoogte riem (mm)	13
Breedte riem (mm)	48
Standaard	DIN7753
Minimale diameter pulley (mm)	140
Antistatisch	Nee
Binnenlengte (mm)	3750
Spoorlengte (mm)	3790
Materiaal riem	EPDM
Koordmateriaal	Polyester
Eenheden	pc
Riemprofiel	5VX
Ribsteek (S) (mm)	17.5
Ribbreedte riem (mm)	3
Gewicht (kg)	3.388

Omschrijving (EN)	Gates® PowerBand® belts are engineered for drives that are subject to pulsating loads, shock loads or extreme vibrations. By joining several Quad-Power® 4 V-belts together the Quad-Power® 4 PowerBand® offers a maintenance-free solution for drives where single belts vibrate, turn over or jump off the pulleys. It comes with all of the advantages of the single belt: this SERVICE FREE EPDM belts are designed to extend product life time eliminating costly downtime for re-tensioning, repair and replacement. PowerBand® construction is built as one solid unit, controlling the belt-to-belt distance and preventing sideways bending. Service-free PowerBand® V-belt with high stability on the toughest drives. Provides excellent resistance against vibrations and shock loads.
Minimale temperatuur (°C)	-50
Maximale temperatuur (°C)	+130
EAN-code	5412571097924
Aangepaste code	4010.3900.90
pitchLength(1_10 inch)	1500
numberOfRibs	3
Status	Normal
oringColour	BLACK
Land van herkomst	US
Constructie	Banded
beltInside	Notched
beltBackSide	Smooth
OC(mm)	3810
Hoek	40
Bereik/ROHS-conformiteit	REACH and RoHS 2
ISO1-standaard	1813
ISO2-standaard	4184
Merk	GATES

Beschrijving

5VX1500/3 GATES Quad-Power™ 4 Powerband™ Banded V-belts

Product URL

<https://aandrijftechniek.nl/product/5vx1500-3-gates-quad-power-4-powerband-banded-v-belts-gates/>