

81013774 IWIS Roller chains IWIS

SKU: 9100060HV-1



Specificaties

Kettingsontwerp	Simplex
Kettingsmering	elidurplus
Corrosiebestendig	Nee
Rechte zijplaten	Nee
Minimale breekbelasting volgens ISO (kN)	40
Gewicht (kg/m)	1.87
Materiaal	Steel
Spoed (inch)	0.75
Spoed (mm)	19.05
Maximale rollerdikte (D1) (mm)	11.91
Breedte tussen binnenplaten (mm)	12.57
Maximale pennendiameter (D2) (mm)	5.96
Breedte over pennen (B) (mm)	30.2

Maximale hoogte binnenplaat (H2) (mm)	18.1
Onderhoudsvrij	Nee
ISO-standaardmaat	60
ISO-standaard	ISO 606 ANSI
Lageroppervlakte (cm²)	1.16
Eenheden	m
Omschrijving (EN)	ELITE high-performance chains “Heavy” series
ANSI chains, as well as specially strengthened versions of chains manufactured to the European standard are available for applications with extremely high loads. “Heavy” versions of ANSI roller chains have the same dimensions as the corresponding ANSI chains, but with plates of the same thickness as those of the next larger size of chain.
HV series chains are fitted with special case-hardened steel alloy pins, giving the chains not only increased tensile strength, but also extremely high breaking strength values.
The right choice for industrial applications: robust and reliable. All ELITE transmission roller chains are highly pre-tensioned and treated with our special additive chain oil eliDUR+, a high-tech initial lubricant. Non-drip eliDUR+ offers not only the added advantage of improved running characteristics, but also provides better corrosion protection.

ELITE highlights:
Approx. 40% higher breaking strength is applied to pre-stretch our chains by 10% more than required by standard ISO 606Initial lubrication with eliDUR+ ensures extremely high wear resistanceLow run-in elongationTensile strength on average 20% higher than required by standard ISO 606ELITE pins have a smooth, extra- hard surface for increased wear resistanceOperating temperature range with eliDUR+ standard lubrication: - 5 °C to +70 °CAll versions also available in coated formIf required, we can deliver your chains ready-made to the desired lengthSpecial lubricants for low temperatures down to -30 °C or high temperature applications up to +250 °C available on requestOn request, iwis delivers chains pair-matched or set-matched and marked
Dikte (t) (mm)	3.2
accToISO606kN	40
accToANSIkN	40
Merk	IWIS
Gewicht (kg/m)	1.87
Materiaal	Steel
Spoed (inch)	0.75
Spoed (mm)	19.05
Dikte (t) (mm)	3.2

Beschrijving

81013774 IWIS Roller chains

Product URL

<https://aandrijftechniek.nl/product/81013774-iwis-roller-chains-iwis/>