

BC10-4-3-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610BC1043A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	15
Buitendiameter (inch)	0.59
Gewicht (kg)	0.008
nmax(rpm)	10000
AngularMisalignmentDeg	1.5
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	0.6
UPC	634529062531
TariffCode	8483.60.8000
boreB1Inch	0.25
ForgedClampScrew	M2
NumberofScrewsEa	2
BoreTolerance	+0.001 in / -0.000 in

FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.0000 in / -0.0005 in
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.001070 lb-in ²
Length(L)	1.076 in (27.3 mm)
boreB2Inch	0.1875
StaticTorqueInput	22 lb-in
NonReversingTorqueInput	11 lb-in
ReversingTorqueInput	5.5 lb-in
TorsionalStiffnessInput	72 lb-in/Deg
ParallelMisalignmentInch	0.004
AxialMotionInput	0.008 in
Bore1ShaftPenetrationInput	0.517 in
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

BC10-4-3-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/bc10-4-3-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>