

BC12-3-3-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610BC1233A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	19.1
Buitendiameter (inch)	0.75
Gewicht (kg)	0.018
nmax(rpm)	10000
AngularMisalignmentDeg	1.5
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	1.21
UPC	634529062555
TariffCode	8483.60.8000
boreB1Inch	0.1875
ForgedClampScrew	M2.5
NumberofScrewsEa	2
BoreTolerance	+0.001 in / -0.000 in

FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.0000 in / -0.0005 in
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.003083 lb-in ²
Length(L)	1.306 in (33.2 mm)
boreB2Inch	0.1875
StaticTorqueInput	40 lb-in
NonReversingTorqueInput	20 lb-in
ReversingTorqueInput	10 lb-in
TorsionalStiffnessInput	120 lb-in/Deg
ParallelMisalignmentInch	0.004
AxialMotionInput	0.010 in
Bore1ShaftPenetrationInput	0.570 in
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

BC12-3-3-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/bc12-3-3-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>