

BC16-6-6-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610BC1666A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	25.4
Buitendiameter (inch)	1
Gewicht (kg)	0.032
nmax(rpm)	10000
AngularMisalignmentDeg	1.5
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
UPC	634529062661
TariffCode	8483.60.8000
boreB1Inch	0.375
ForgedClampScrew	M3
NumberofScrewsEa	2
BoreTolerance	+0.001 in / -0.000 in

FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.0000 in / -0.0005 in
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.009289 lb-in ²
Length(L)	1.345 in (34.2 mm)
boreB2Inch	0.375
StaticTorqueInput	60 lb-in
NonReversingTorqueInput	30 lb-in
ReversingTorqueInput	15 lb-in
TorsionalStiffnessInput	244 lb-in/Deg
ParallelMisalignmentInch	0.004
AxialMotionInput	0.012 in
Bore1ShaftPenetrationInput	0.626 in
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

BC16-6-6-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/bc16-6-6-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>