

BC21-6-5-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610BC2165A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	33.3
Buitendiameter (inch)	1.313
Gewicht (kg)	0.071
nmax(rpm)	10000
AngularMisalignmentDeg	1.5
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
UPC	634529062760
TariffCode	8483.60.8000
boreB1Inch	0.375
ForgedClampScrew	M3
NumberofScrewsEa	2
BoreTolerance	+0.001 in / -0.000 in

FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.0000 in / -0.0005 in
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.037385 lb-in ²
Length(L)	1.700 in (43.2 mm)
boreB2Inch	0.3125
StaticTorqueInput	120 lb-in
NonReversingTorqueInput	60 lb-in
ReversingTorqueInput	30 lb-in
TorsionalStiffnessInput	400 lb-in/Deg
ParallelMisalignmentInch	0.006
AxialMotionInput	0.016 in
Bore1ShaftPenetrationInput	0.804 in
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

BC21-6-5-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/bc21-6-5-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>