

BC26-6-6-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610BC2666A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	41.3
Buitendiameter (inch)	1.625
Gewicht (kg)	0.138
nmax(rpm)	10000
AngularMisalignmentDeg	2
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4.6
UPC	634529062883
TariffCode	8483.60.8000
boreB1Inch	0.375
ForgedClampScrew	M4
NumberofScrewsEa	2
BoreTolerance	+0.001 in / -0.000 in

FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.0000 in / -0.0005 in
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.106233 lb-in ²
Length(L)	2.035 in (51.7 mm)
boreB2Inch	0.375
StaticTorqueInput	250 lb-in
NonReversingTorqueInput	125 lb-in
ReversingTorqueInput	62.5 lb-in
TorsionalStiffnessInput	550 lb-in/Deg
ParallelMisalignmentInch	0.01
AxialMotionInput	0.020 in
Bore1ShaftPenetrationInput	0.946 in
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

BC26-6-6-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/bc26-6-6-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>