

# BC32-12-8-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610BC32128A



## Extra afbeelding



## Specificaties

|                               |                       |
|-------------------------------|-----------------------|
| <b>Materiaal</b>              | Aluminium             |
| <b>Buitendiameter (mm)</b>    | 50.8                  |
| <b>Buitendiameter (inch)</b>  | 2                     |
| <b>Gewicht (kg)</b>           | 0.218                 |
| <b>nmax(rpm)</b>              | 10000                 |
| <b>AngularMisalignmentDeg</b> | 2                     |
| <b>ScrewType</b>              | Alloy Steel           |
| <b>ScrewFinish</b>            | Black Oxide           |
| <b>SeatingTorqueNm</b>        | 9.5                   |
| <b>UPC</b>                    | 634529067581          |
| <b>TariffCode</b>             | 8483.60.8000          |
| <b>boreB1Inch</b>             | 0.75                  |
| <b>ForgedClampScrew</b>       | M5                    |
| <b>NumberofScrewsEa</b>       | 2                     |
| <b>BoreTolerance</b>          | +0.001 in / -0.000 in |

|                                   |                             |
|-----------------------------------|-----------------------------|
| <b>FinishSpecification</b>        | Anodize                     |
| <b>Style</b>                      | Clamp                       |
| <b>ShaftTolerance</b>             | +0.0000 in / -0.0005 in     |
| <b>FasteningDimensions</b>        | Metric                      |
| <b>ISO 9001 (2008)</b>            | Yes                         |
| <b>REACH</b>                      | Yes                         |
| <b>ROHS2</b>                      | Yes                         |
| <b>ConflictMinerals</b>           | Yes                         |
| <b>MomentofInertia</b>            | 0.277823 lb-in <sup>2</sup> |
| <b>Length(L)</b>                  | 2.413 in (61.3 mm)          |
| <b>boreB2Inch</b>                 | 0.5                         |
| <b>StaticTorqueInput</b>          | 400 lb-in                   |
| <b>NonReversingTorqueInput</b>    | 200 lb-in                   |
| <b>ReversingTorqueInput</b>       | 100 lb-in                   |
| <b>TorsionalStiffnessInput</b>    | 950 lb-in/Deg               |
| <b>ParallelMisalignmentInch</b>   | 0.01                        |
| <b>AxialMotionInput</b>           | 0.020 in                    |
| <b>Bore1ShaftPenetrationInput</b> | 1.099 in                    |
| <b>BellowsAttachmentMethod</b>    | Epoxy                       |
| <b>UNSPC</b>                      | 31163018                    |
| <b>Merk</b>                       | Ruland Manufacturing        |

## Beschrijving

BC32-12-8-A Ruland Manufacturing Bellow couplings

## Product URL

<https://aandrijftechniek.nl/product/bc32-12-8-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>