

BC32-16-12-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610BC321612A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	50.8
Buitendiameter (inch)	2
Gewicht (kg)	0.197
nmax(rpm)	10000
AngularMisalignmentDeg	2
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	9.5
UPC	634529062043
TariffCode	8483.60.8000
boreB1Inch	1
ForgedClampScrew	M5
NumberofScrewsEa	2
BoreTolerance	+0.001 in / -0.000 in

FinishSpecification	Anodize
Style	Clamp
ShaftTolerance	+0.0000 in / -0.0005 in
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.270755 lb-in ²
Length(L)	2.413 in (61.3 mm)
boreB2Inch	0.75
StaticTorqueInput	400 lb-in
NonReversingTorqueInput	200 lb-in
ReversingTorqueInput	100 lb-in
TorsionalStiffnessInput	950 lb-in/Deg
ParallelMisalignmentInch	0.01
AxialMotionInput	0.020 in
Bore1ShaftPenetrationInput	1.099 in
BellowsAttachmentMethod	Epoxy
UNSPC	31163018
Merk	Ruland Manufacturing

Beschrijving

BC32-16-12-A Ruland Manufacturing Bellow couplings

Product URL

<https://aandrijftechniek.nl/product/bc32-16-12-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>