

# BCK32-8-8-A Ruland Manufacturing Bellow couplings Ruland Manufacturing

SKU: 610BCK3288A



## Extra afbeelding



## Specificaties

|                        |                       |
|------------------------|-----------------------|
| Materiaal              | Aluminium             |
| Buitendiameter (mm)    | 50.8                  |
| Buitendiameter (inch)  | 2                     |
| Gewicht (kg)           | 0.226                 |
| nmax(rpm)              | 10000                 |
| AngularMisalignmentDeg | 2                     |
| ScrewType              | Alloy Steel           |
| ScrewFinish            | Black Oxide           |
| SeatingTorqueNm        | 9.5                   |
| UPC                    | 634529167502          |
| TariffCode             | 8483.60.8000          |
| boreB1Inch             | 0.5                   |
| ForgedClampScrew       | M5                    |
| NumberofScrewsEa       | 2                     |
| BoreTolerance          | +0.001 in / -0.000 in |

|                                   |                           |
|-----------------------------------|---------------------------|
| <b>FinishSpecification</b>        | Anodize                   |
| <b>Style</b>                      | Clamp                     |
| <b>ShaftTolerance</b>             | +0.0000 in / -0.0005 in   |
| <b>FasteningDimensions</b>        | Metric                    |
| <b>ISO 9001 (2008)</b>            | Yes                       |
| <b>REACH</b>                      | Yes                       |
| <b>ROHS2</b>                      | Yes                       |
| <b>ConflictMinerals</b>           | Yes                       |
| <b>MomentofInertia</b>            | 0.2808 lb-in <sup>2</sup> |
| <b>Length(L)</b>                  | 2.413 in (61.3 mm)        |
| <b>Keyway(K1)</b>                 | 1/8 in                    |
| <b>Keyway(K2)</b>                 | 1/8 in                    |
| <b>boreB2Inch</b>                 | 0.5                       |
| <b>StaticTorqueInput</b>          | 400 lb-in                 |
| <b>NonReversingTorqueInput</b>    | 200 lb-in                 |
| <b>ReversingTorqueInput</b>       | 100 lb-in                 |
| <b>TorsionalStiffnessInput</b>    | 950 lb-in/Deg             |
| <b>ParallelMisalignmentInch</b>   | 0.01                      |
| <b>AxialMotionInput</b>           | 0.020 in                  |
| <b>Bore1ShaftPenetrationInput</b> | 1.099 in                  |
| <b>BellowsAttachmentMethod</b>    | Epoxy                     |
| <b>UNSPC</b>                      | 31163018                  |
| <b>Merk</b>                       | Ruland Manufacturing      |

## Beschrijving

BCK32-8-8-A Ruland Manufacturing Bellow couplings

## Product URL

<https://aandrijftechniek.nl/product/bck32-8-8-a-ruland-manufacturing-bellow-couplings-ruland-manufacturing/>