

D390 GATES HI-POWER?? Endless V-belts GATES

SKU: 4G50032X9910



Specificaties

Type riem	Classical wrapped
Hoogte riem (mm)	19
Breedte riem (mm)	32
Antistatisch	Nee
Binnenlengte (mm)	9910
Spoorlengte (mm)	9982
Materiaal riem	Chloroprene
Koordmateriaal	Polyester
Eenheden	pc
Riemprofiel	D
Gewicht (kg)	7.7
Omschrijving (EN)	The wrapped classical section Hi-Power??? V-belt has a long reputation for reliability on agricultural and industrial applications. The arched top of the Hi-Power??? belt provides superior strength to prevent "dishing" and distortion of the tensile section. The cords are properly aligned, each of them carrying its full share of the load. Arched top, concave sidewalls and rounded corners provide uniform tensile loading and uniform pulley sidewall contact for excellent belt service life and reduced pulley wear. The vulcanised Flex-bonded tensile cords provide superior resistance to tensile and flexing forces, fatigue and shock loads. The Flex Weave oil and heat resistant cover protects the belt core from the toughest environments.

Minimale temperatuur (??C)	-30
Maximale temperatuur (??C)	+60
EAN-code	5412571052800
Aangepaste code	4010.3900.90
numberOfRibs	1
Status	Normal
oringColour	BLACK
Land van herkomst	MX
Constructie	Bandless
beltInside	Smooth
beltBackSide	Smooth
OC(mm)	9995
Hoek	39
Bereik/ROHS-conformiteit	REACH and RoHS 2
ISO1-standaard	1813
Merk	GATES
Breedte riem (mm)	32
Antistatisch	Nee
Binnenlengte (mm)	9910
Materiaal riem	Chloroprene
Riemprofiel	D
Gewicht (kg)	7.7
Minimale temperatuur (??C)	-30
Maximale temperatuur (??C)	+60
Land van herkomst	MX

Beschrijving

D390 GATES HI-POWER?? Endless V-belts

Product URL

<https://aandrijftechniek.nl/product/d390-gates-hi-power-endless-v-belts-gates/>