

FCMR16-5-5-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FCMR1655SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.625
Gewicht (kg)	0.0287
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	15.9
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	5
boreB2Mm	5
lengthLInch	1
lengthLMm	25.4
ClearanceDiameterMm	20.22
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	12.3
Bore2ShaftPenetrationMm	12.3

StaticTorqueNm	2.04
NonReversingTorqueNm	1.02
ReversingTorqueNm	0.51
TorsionalStiffnessDeg/Nm	0.78
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.13
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M2.5
ScrewType	Stainless Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	1.21
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529043141
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FCMR16-5-5-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fcmr16-5-5-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>