

FCMR19-6-5-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FCMR1965SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.75
Gewicht (kg)	0.0543
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	19.1
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	6
boreB2Mm	5
lengthLInch	1.25
lengthLMm	31.8
ClearanceDiameterMm	22.33
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	15.4
Bore2ShaftPenetrationMm	15.4

StaticTorqueNm	4.64
NonReversingTorqueNm	2.32
ReversingTorqueNm	1.16
TorsionalStiffnessDeg/Nm	0.7
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.13
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M3
ScrewType	Alloy Steel with Nypatch
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529043189
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FCMR19-6-5-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fcmr19-6-5-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>