

# FCMR19-8-8-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FCMR1988A



## Extra afbeelding



## Specificaties

<b>Buitendiameter (inch)</b>	0.75
<b>Gewicht (kg)</b>	0.0185
<b>CouplingMaterial</b>	Aluminum
<b>noOfScrews</b>	2
<b>D2OuterDiameterOD</b>	19.1
<b>nmax(rpm)</b>	6000
<b>UNSPSCcode</b>	31163003
<b>boreB1Mm</b>	8
<b>boreB2Mm</b>	8
<b>lengthLInch</b>	1.25
<b>lengthLMm</b>	31.8
<b>ClearanceDiameterMm</b>	22.33
<b>MaterialSpecification</b>	7075-T651 Bar
<b>Bore1ShaftPenetrationMm</b>	15.4
<b>Bore2ShaftPenetrationMm</b>	15.4

<b>StaticTorqueNm</b>	2.26
<b>NonReversingTorqueNm</b>	1.13
<b>ReversingTorqueNm</b>	0.57
<b>TorsionalStiffnessDeg/Nm</b>	2.04
<b>AngularMisalignmentDeg</b>	3
<b>ParallelMisalignmentMm</b>	0.2
<b>AxialMotionMm</b>	0.13
<b>couplingBoreTolerance</b>	+0.025 mm / -0.000 mm
<b>couplingShaftTolerance</b>	+0.000 mm / -0.013 mm
<b>ScrewCapSize</b>	M3
<b>ScrewType</b>	Alloy Steel with Nypatch
<b>ScrewFinish</b>	Black Oxide
<b>SeatingTorqueNm</b>	2.1
<b>certifications</b>	ISO-9001-2008 REACH ROHS2 Conflict Minerals
<b>UPC</b>	634529007464
<b>TariffCode</b>	8483.60.8000
<b>Merk</b>	Ruland Manufacturing

## Beschrijving

FCMR19-8-8-A Ruland Manufacturing Beam couplings

## Product URL

<https://aandrijftechniek.nl/product/fcmr19-8-8-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>