


FCMR25-11-11-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FCMR251111SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	1
Gewicht (kg)	0.1006
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	25.4
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	11
boreB2Mm	11
lenghtLInch	1.5
lenghtLMm	38.1
ClearanceDiameterMm	28.37
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	18.3
Bore2ShaftPenetrationMm	18.3

StaticTorqueNm	4.4
NonReversingTorqueNm	2.2
ReversingTorqueNm	1.1
TorsionalStiffnessDeg/Nm	0.74
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M4
ScrewType	Alloy Steel with Nypatch
ScrewFinish	Black Oxide
SeatingTorqueNm	4.6
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529043318
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FCMR25-11-11-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fcmr25-11-11-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>