

FCMR25-6-6-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FCMR2566A



Extra afbeelding



Specificaties

Buitendiameter (inch)	1
Gewicht (kg)	0.0459
CouplingMaterial	Aluminum
noOfScrews	2
D2OuterDiameterOD	25.4
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	6
boreB2Mm	6
lengthLInch	1.5
lengthLMm	38.1
ClearanceDiameterMm	28.37
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	18.3
Bore2ShaftPenetrationMm	18.3

StaticTorqueNm	4.42
NonReversingTorqueNm	1.98
ReversingTorqueNm	0.99
TorsionalStiffnessDeg/Nm	0.55
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M4
ScrewType	Alloy Steel with Nypatch
ScrewFinish	Black Oxide
SeatingTorqueNm	4.6
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529007655
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FCMR25-6-6-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fcmr25-6-6-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>