

FCMR32-13-13-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FCMR321313A



Extra afbeelding



Specificaties

Buitendiameter (inch)	1.25
Gewicht (kg)	0.0712
CouplingMaterial	Aluminum
noOfScrews	2
D2OuterDiameterOD	31.8
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	13
boreB2Mm	13
lengthLInch	1.75
lengthLMm	44.5
ClearanceDiameterMm	37.06
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	21.4
Bore2ShaftPenetrationMm	21.4

StaticTorqueNm	5.8
NonReversingTorqueNm	2.9
ReversingTorqueNm	1.45
TorsionalStiffnessDeg/Nm	0.71
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M5
ScrewType	Alloy Steel with Nypatch
ScrewFinish	Black Oxide
SeatingTorqueNm	9.5
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529137420
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FCMR32-13-13-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fcmr32-13-13-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>