

FCMR32-13-13-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FCMR321313SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	1.25
Gewicht (kg)	0.1906
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	31.8
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	13
boreB2Mm	13
lengthLInch	1.75
lengthLMm	44.5
ClearanceDiameterMm	37.06
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	21.4
Bore2ShaftPenetrationMm	21.4

StaticTorqueNm	11.32
NonReversingTorqueNm	5.66
ReversingTorqueNm	2.83
TorsionalStiffnessDeg/Nm	0.33
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M5
ScrewType	Alloy Steel with Nypatch
ScrewFinish	Black Oxide
SeatingTorqueNm	9.5
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529240342
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FCMR32-13-13-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fcmr32-13-13-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>