

# FCMR32-14-14-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FCMR321414SS



## Extra afbeelding



## Specificaties

|                         |                     |
|-------------------------|---------------------|
| Buitendiameter (inch)   | 1.25                |
| Gewicht (kg)            | 0.1867              |
| CouplingMaterial        | 303 Stainless Steel |
| noOfScrews              | 2                   |
| D2OuterDiameterOD       | 31.8                |
| nmax(rpm)               | 6000                |
| UNSPSCcode              | 31163003            |
| boreB1Mm                | 14                  |
| boreB2Mm                | 14                  |
| lengthLInch             | 1.75                |
| lengthLMm               | 44.5                |
| ClearanceDiameterMm     | 37.06               |
| MaterialSpecification   | 303 Stainless Steel |
| Bore1ShaftPenetrationMm | 21.4                |
| Bore2ShaftPenetrationMm | 21.4                |

|                                 |                                             |
|---------------------------------|---------------------------------------------|
| <b>StaticTorqueNm</b>           | 11.32                                       |
| <b>NonReversingTorqueNm</b>     | 5.66                                        |
| <b>ReversingTorqueNm</b>        | 2.83                                        |
| <b>TorsionalStiffnessDeg/Nm</b> | 0.33                                        |
| <b>AngularMisalignmentDeg</b>   | 3                                           |
| <b>ParallelMisalignmentMm</b>   | 0.38                                        |
| <b>AxialMotionMm</b>            | 0.25                                        |
| <b>couplingBoreTolerance</b>    | +0.025 mm / -0.000 mm                       |
| <b>couplingShaftTolerance</b>   | +0.000 mm / -0.013 mm                       |
| <b>ScrewCapSize</b>             | M5                                          |
| <b>ScrewType</b>                | Alloy Steel with Nypatch                    |
| <b>ScrewFinish</b>              | Black Oxide                                 |
| <b>SeatingTorqueNm</b>          | 9.5                                         |
| <b>certifications</b>           | ISO-9001-2008 REACH ROHS2 Conflict Minerals |
| <b>UPC</b>                      | 634529051672                                |
| <b>TariffCode</b>               | 8483.60.8000                                |
| <b>Merk</b>                     | Ruland Manufacturing                        |

## Beschrijving

FCMR32-14-14-SS Ruland Manufacturing Beam couplings

## Product URL

<https://aandrijftechniek.nl/product/fcmr32-14-14-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>