

FCMR38-17-12-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FCMR381712SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	1.5
Gewicht (kg)	0.3426
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	38.1
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	17
boreB2Mm	12
lengthLInch	2.25
lengthLMm	57.2
ClearanceDiameterMm	41.71
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	27.3
Bore2ShaftPenetrationMm	27.3

StaticTorqueNm	16.38
NonReversingTorqueNm	8.19
ReversingTorqueNm	4.1
TorsionalStiffnessDeg/Nm	0.4
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.76
AxialMotionMm	0.38
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewCapSize	M6
ScrewType	Alloy Steel with Nypatch
ScrewFinish	Black Oxide
SeatingTorqueNm	16
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529209868
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FCMR38-17-12-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fcmr38-17-12-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>