

FSMR16-6-6-SS Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FSMR1666SS



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.625
Gewicht (kg)	0.0304
CouplingMaterial	303 Stainless Steel
noOfScrews	2
D2OuterDiameterOD	15.9
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	6
boreB2Mm	6
lengthLInch	1
lengthLMm	25.4
MaterialSpecification	303 Stainless Steel
Bore1ShaftPenetrationMm	12.3
Bore2ShaftPenetrationMm	12.3
StaticTorqueNm	2.04

NonReversingTorqueNm	1.02
ReversingTorqueNm	0.51
TorsionalStiffnessDeg/Nm	0.78
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.13
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	1.76
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529045992
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FSMR16-6-6-SS Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fsmr16-6-6-ss-ruland-manufacturing-beam-couplings-ruland-manufacturing/>