

FSMR19-6-5-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FSMR1965A



Extra afbeelding



Specificaties

Buitendiameter (inch)	0.75
Gewicht (kg)	0.0206
CouplingMaterial	Aluminum
noOfScrews	2
D2OuterDiameterOD	19.1
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	6
boreB2Mm	5
lenghtLInch	1.25
lenghtLMm	31.8
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	15.4
Bore2ShaftPenetrationMm	15.4
StaticTorqueNm	2.94

NonReversingTorqueNm	1.47
ReversingTorqueNm	0.74
TorsionalStiffnessDeg/Nm	1.33
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.2
AxialMotionMm	0.13
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	1.76
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529010495
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FSMR19-6-5-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fsmr19-6-5-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>