

FSMR25-9-8-A Ruland Manufacturing Beam couplings Ruland Manufacturing

SKU: 610FSMR2598A



Extra afbeelding



Specificaties

Buitendiameter (inch)	1
Gewicht (kg)	0.0435
CouplingMaterial	Aluminum
noOfScrews	4
D2OuterDiameterOD	25.4
nmax(rpm)	6000
UNSPSCcode	31163003
boreB1Mm	9
boreB2Mm	8
lengthLInch	1.5
lengthLMm	38.1
MaterialSpecification	7075-T651 Bar
Bore1ShaftPenetrationMm	18.3
Bore2ShaftPenetrationMm	18.3
StaticTorqueNm	3.73

NonReversingTorqueNm	1.87
ReversingTorqueNm	0.93
TorsionalStiffnessDeg/Nm	0.86
AngularMisalignmentDeg	3
ParallelMisalignmentMm	0.38
AxialMotionMm	0.25
couplingBoreTolerance	+0.025 mm / -0.000 mm
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4
certifications	ISO-9001-2008 REACH ROHS2 Conflict Minerals
UPC	634529010839
TariffCode	8483.60.8000
Merk	Ruland Manufacturing

Beschrijving

FSMR25-9-8-A Ruland Manufacturing Beam couplings

Product URL

<https://aandrijftechniek.nl/product/fsmr25-9-8-a-ruland-manufacturing-beam-couplings-ruland-manufacturing/>